



## SolarEdge Single Phase Inverters

SE2200H, SE3000H, SE3500H, SE3680H  
SE4000H, SE5000H, SE6000H



INVERTERS

### Optimized installation with HD-Wave technology

- Specifically designed to work with power optimizers
- Record-breaking efficiency
- Extremely small, lightweight and easy to install
- High reliability without any electrolytic capacitors
- Built-in module-level monitoring
- Outdoor and indoor installation
- Compatible with the StorEdge Interface for Smart Energy Management StorEdge™ applications





# Single Phase Inverters

SE2200H, SE3000H, SE3500H, SE3680H  
SE4000H, SE5000H, SE6000H

	SE2200H	SE3000H	SE3500H	SE3680H	SE4000H	SE5000H	SE6000H	
<b>OUTPUT</b>								
Rated AC Power Output	2200	3000	3500	3680	4000	5000 <sup>(1)</sup>	6000	VA
Maximum AC Power Output	2200	3000	3500	3680	4000	5000 <sup>(1)</sup>	6000	VA
AC Output Voltage (nominal)	220 / 230							Vac
AC Output Voltage Range	184 - 264.5							Vac
AC Frequency (nominal)	50 / 60 ± 5							Hz
Maximum Continuous Output Current	10	14	16	16	18.5	23	27.5	A
Residual Current Detector / Residual Current Step Detector	300 / 30							mA
Utility Monitoring, Islanding Protection, Country Configurable Thresholds	Yes							
<b>INPUT</b>								
Maximum DC Power	3400	4650	5425	5700	6200	7750	9300	W
Transformer-less, Ungrounded	Yes							
Maximum Input Voltage	480							Vdc
Nominal DC Input Voltage	380							Vdc
Maximum Input Current	6.5	9	10	10.5	11.5	13.5	16.5	Adc
Reverse-Polarity Protection	Yes							
Ground-Fault Isolation Detection	600kΩ Sensitivity							
Maximum Inverter Efficiency	99.2							%
European Weighted Efficiency	98.3	98.8				99		%
Nighttime Power Consumption	< 2.5							W
<b>ADDITIONAL FEATURES</b>								
Supported Communication Interfaces	RS485, Ethernet, ZigBee (optional), WiFi (optional), Cellular (optional)							
Smart Energy Management	Export Limitation, StorEdge applications							
<b>STANDARD COMPLIANCE</b>								
Safety	IEC-62109-1/2, AS-3100							
Grid Connection Standards	AS-4777, VDE-AR-N-4105, VDE 0126-1-1, UTE C15-712, G83/2, G59/3, CEI-021, EN 50438, IEC61727, IEC62116, ÖNORM, TF3.2.1, C10-11, NRS 097-2-1							
Emissions	IEC61000-6-2, IEC61000-6-3, IEC61000-3-11, IEC61000-3-12, FCC Part 15 Class B							
<b>INSTALLATION SPECIFICATIONS</b>								
AC Output - Supported Cable Diameter	9 - 16							mm
AC - Supported Wire Cross Section	1 - 16							mm <sup>2</sup>
DC Input	1 x MC4			2 x MC4 pair				
Dimensions (H x W x D)	280 x 370 x 142							mm
Noise	< 25							dBA
Weight	9.5							kg
Cooling	Natural Convection							
Operating Temperature Range	-20 to +60 <sup>(2)</sup> (-40°C option)							°C
Protection Rating	IP65 - Outdoor and Indoor							

<sup>(1)</sup> 4600VA in Germany  
<sup>(2)</sup> De-rating from 50°C



**RoHS**



**IjsselEnergie**